



DISPLAY

| | |
|----------------------|---|
| Diagonal Size | 65" 4K, 75" 4K, 86" 4K |
| Screen Type | TFT LCD (Direct LED Backlight) |
| Aspect Ratio | 16:9 |
| Display Area | 65" 4K: 1429 x 804 mm (56.3 x 31.7 in) 75" 4K: 1652 x 930 mm (65 x 36.6 in) 86" 4K: 1895 x 1066 mm (74.6 x 41.9 in) |
| Display Colours | 1.07 Billion |
| Resolution | 4K UHD (3840 x 2160 @ 60 Hz) |
| Response Time | 8 ms |
| Panel Refresh Rate | 60 Hz |
| LED Lifespan | 50,000 hours |
| LCD Viewing Angle | 178° |
| Brightness | 65" 4K: 350 cd/m2 75" 4K: 350 cd/m2 86" 4K: 400 cd/m2 |
| Contrast Ratio | 4000:1 |
| Ambient Light Sensor | Yes |
| Glass Hardness | 9H (pencil), 7 (Mohs) |
| Glass Type | Heat-tempered, Anti-Glare |

INTERACTIVITY

| | |
|-------------------------------|--|
| Front Facing Controls | Yes, with Power, Menu, Volume Controls, Source Selection |
| Touch Technology | Vellum™ Writing Technology |
| Continuous Touch Points | 15 |
| Touch Resolution | 32768 x 32768 px |
| Response Time | 10 ms |
| Touch Accuracy | 1 mm |
| Tracking Rate | 4 m/s |
| Scan Rate | 100 Hz |
| Gestures and Edge Swipes | Windows® Supported |
| Pens Included | 1 |
| Pen Type | Battery-less Pen |
| Pen Holder | Integrated Full-length Pen Tray |
| Pen Tip Diameter | 3 mm |
| Pen and Touch Differentiation | No |
| Palm Detection | Yes |
| Annotation Over Any Source | Yes |
| Classroom Essential Apps | Including Whiteboard, Annotate, Timer, Spinner, Screen Capture, Screen Share, Browser, PDF Reader, Media Players |
| Compatibility | Windows® 8 to 10; OS X® 10.8 to 10.11; macOS® Sierra 10.12.1 or later; Linux® Ubuntu® 18.04 LTS; Chrome OS™ |

CONNECTIVITY

| | |
|--|----------------|
| HDMI® 2.0 In (Rear) | 1 |
| HDMI 2.0 In (Front) | 1 |
| VGA In | 1 |
| VGA Audio In | 1 |
| USB-A 2.0 (Rear) | 1 |
| USB-A 2.0 (Front) | 1 |
| USB-A 3.0 (faster data transfer, Front) | 1 (OPS) |
| USB-B Touch (Rear) | 1 |
| USB-B Touch (Front) | 1 |
| USB-C PD2.0, USB 2.0, DP1.2 (Rear) | 1 |
| LAN In (RJ45) | 1x 10/100 Mbps |
| LAN Out (RJ45) | 1x 10/100 Mbps |
| Wake-on-LAN | Yes |
| Wi-Fi® Module IEEE® 802.11a/b/g/n/ac Wireless, 2x2 | Optional |
| RS-232 | Yes |
| CVBS | 1 |
| Mic In (3.5 mm) | 1 |
| Headphone | 1 |
| OPS Slot | 1 |

COMPUTING

| | |
|-----------------------------|---|
| Operating System | Android™ Oreo 8 |
| RAM | 2 GB |
| Internal Storage | 16 GB |
| CPU | Quad Core: (2) ARM Cortex A73, (2) ARM Cortex A53 |
| GPU | ARM Mali-G51 MP2 |
| Remote Over-the-Air Updates | Yes |
| Promethean Panel Management | Yes |

AUDIO

| | |
|----------------------------|--------------|
| Dual Front Facing Speakers | 2 x 15 Watts |
|----------------------------|--------------|

POWER

| | |
|-----------------------------|---|
| Power Requirements | 100V - 240V AC |
| Power Consumption (Typical) | 65" 4K: 107 W 75" 4K: 107 W 86" 4K: 159 W |
| Power Consumption (Standby) | <=0.5 W |
| Ultra-Quiet Fanless Design | Yes |

ENVIRONMENTAL

| | |
|-----------------------|------------------------------------|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -15°C to 55°C (-5°F to 131°F) |
| Operating Humidity | 20% to 80% non-condensing humidity |
| Storage Humidity | 20% to 90% non-condensing humidity |

PHYSICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Panel Dimensions | 65" 4K: 1536 x 960 x 90 mm (60.5 x 37.8 x 3.5 in) |
| | 75" 4K: 1767 x 1093 x 106 mm (69.6 x 43.0 x 4.2 in) |
| | 86" 4K: 2018 x 1236 x 113 mm (79.4 x 48.7 x 4.4 in) |
| Packed Dimensions | 65" 4K: 1720 x 1095 x 272 mm (67.7 x 43.1 x 10.7 in) |
| | 75" 4K: 1880 x 1160 x 320 mm (74.0 x 45.7 x 12.6 in) |
| | 86" 4K: 2140 x 1340 x 280 mm (84.3 x 52.8 x 11.0 in) |
| Net Weight | 65" 4K: 46 kg (101 lbs) |
| | 75" 4K: 62 kg (137 lbs) |
| | 86" 4K: 82 kg (181 lbs) |
| Packed Weight | 65" 4K: 57 kg (126 lbs) |
| | 75" 4K: 77 kg (170 lbs) |
| | 86" 4K: 100 kg (220 lbs) |
| Wall Mount Dimensions | 1010 x 720 x 52 mm (39.8 x 28.3 x 2.0 in) |
| VESA Mount Point | 65" 4K: 600 x 400 mm (23.6 x 15.7 in) |
| | 75" 4K: 600 x 400 mm (23.6 x 15.7 in) |
| | 86" 4K: 700 x 400 mm (27.6 x 15.7 in) |

COMPLIANCE & CERTIFICATION

| | |
|---------------------------|-------------------------------|
| Regulatory Certifications | CE, FCC, IC, UL, CUL, CB, RCM |
| Energy Star Certified | 65" 4K: Yes |
| | 75" 4K: Yes |
| | 86" 4K: Yes |

EDUCATION SOFTWARE LICENCE

| | |
|--|----------|
| ActivInspire® Professional Single User | Included |
|--|----------|

PACKED CONTENTS

| | |
|-------------------------|--|
| What's in the Box (1) | (1) ActivPanel Nickel |
| | (1) 3M Length HDMI Cable |
| | (1) 3M Length USB Cable (A-B) |
| | (1) 3M Regional Power Cable |
| | (1) 2M Length USB-C Cable |
| | (1) Remote Control |
| | (2) Batteries for Remote Control |
| | (1) ActivPanel Nickel Pen |
| | (1) Sealed Antistatic Bag |
| | (4) VESA mount screws (M6) |
| | (1) Mini PC Bracket with screws |
| (1) Quick Install Guide | |
| What's in the Box (2) | (1) Promethean Wi-Fi Module (Ni/Co) |
| | (2) Antenna |
| | (1) Promethean Wi-Fi Module (Ni/Co) User Guide |

INSTALLATION

The installation of this product should be completed by a qualified installer. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance, safety and warranty. For more information, visit Support.PrometheanWorld.com.

WARRANTY

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information and visit PrometheanWorld.com/Warranty.


SUPPORT

For all Promethean products, visit Support.PrometheanWorld.com.

TECHNICAL DRAWINGS


65" 4K

Front




| DIM | DIMENSION (MM) | DIMENSION (IN) |
|-------|----------------|----------------|
| A | 1641 | 64.6 |
| B | 1430 | 56.3 |
| C | 805 | 31.7 |
| D | 1101 | 43.3 |
| E | 133 | 5.2 |
| F | 83 | 3.3 |
| G | 960 | 37.8 |
| H | 1536 | 60.5 |
| I | 600 | 23.6 |
| J Min | 151 | 5.9 |
| J Max | 289 | 11.4 |
| K Min | 1151 | 45.3 |
| K Max | 1289 | 50.7 |
| L | 90 | 3.5 |

Back




Side



TECHNICAL DRAWINGS


75"

Front




| DIM | DIMENSION (MM) | DIMENSION (IN) |
|-------|----------------|----------------|
| A | 1895 | 74.6 |
| B | 1652 | 65.0 |
| C | 929 | 36.6 |
| D | 1105 | 43.5 |
| E | 144 | 5.7 |
| F | 76 | 3.0 |
| G | 1093 | 43.0 |
| H | 1767 | 69.6 |
| I | 600 | 23.6 |
| J Min | 228 | 9.0 |
| J Max | 365 | 14.4 |
| K Min | 1228 | 48.3 |
| K Max | 1365 | 53.7 |
| L | 106 | 4.2 |

Back



Side




ActivPanel 2019-E Nickel SS 05/21 v1.5a EN-GB

Page 4

TECHNICAL DRAWINGS


86"

Front




| DIM | DIMENSION (MM) | DIMENSION (IN) |
|-------|----------------|----------------|
| A | 2177 | 85.7 |
| B | 1897 | 74.7 |
| C | 1067 | 42.0 |
| D | 1107 | 43.6 |
| E | 155 | 6.1 |
| F | 78 | 3.1 |
| G | 1236 | 48.7 |
| H | 2018 | 79.4 |
| I | 700 | 27.6 |
| J Min | 292 | 11.5 |
| J Max | 430 | 16.9 |
| K Min | 1292 | 50.9 |
| K Max | 1430 | 56.3 |
| L | 113 | 4.4 |

Back



Side



ActivPanel 2019-E Nickel SS 05/21 v1.5a EN-GB

Page 5